

## NCC PORCELAIN PROTECTOR

Water based pre-grout treatment.

### Interior & exterior use

For use on all types of textured porcelain tile surfaces. Helps with grout and jointing compound release. On exterior surfaces a further coat can be applied after grouting, which will help with the removal of stains from organic matter.

## Directions for use

### Preparation:

Ensure surface to be treated is completely clean, dry and free from dirt, grime, cement and grout. If necessary, first wash surfaces with a dilute solution of NCC Cement, Grout & Salt Remover 1:5 and white pad or scrubbing brush. Rinse well to remove residues and leave to dry

**Application:** Shake bottle before use. Before grouting apply evenly to the surface using a broad paint brush, foam roller or light pressure sprayer. Allow to dry for 30 minutes. Apply a second coat. Leave to cure for a minimum of 1 hour before *grouting or pointing*. Once pointing is dry and all residues have been removed a further coat of protector can be applied covering the joints as well. Hard to remove dried on cement stains can be removed using NCC Cement, Grout & Salt Remover.

Hard to remove stains from jointing compounds can be removed using NCC Resin Residue Remover.

## Coverage: M<sup>2</sup> per application

	1 LTR	5 LTR	25 LTR
Low porosity surfaces	30m <sup>2</sup>	150m <sup>2</sup>	N/A

## Storage information

Store in a cool, dry, frost-free environment. Store locked up. Shelf Life – Up to 2 years for un-opened containers. Once opened use within 6 months of purchase for optimum results. Empty containers are recyclable. Active ingredients are water soluble and inert once cured so therefore not harmful to the environment and ecologically sound.

## Other

Do not use in temperatures under 5°C or over 25°C. The surface of the tiles should be cool. Clean application tools and equipment with clean water after use.

## Health, Safety & Environmental

Keep out of reach of children.  
Dispose of content/container to hazardous or special waste collection point.



This information is offered without guarantee. The material should be used so as to take account of the local conditions and the surfaces to be treated. In case of doubt, the product should be tried out in an inconspicuous area