

Technical Information Sheet
Article No. AMT103

Easy-Peel Cleaner

Brush On, Peel Off Cleaner

Easy Peel	Art. No. AMT103
Activator for Marble	Art. No. AMT283B
Activator for Stone	Art. No. AMT583B

Range of use

Easy-Peel is a fast skinning cleaning latex for thorough removal of dust, soot, fire damage, nicotine residue and other soiling without using water.

It can be used on most surfaces including fireplace surrounds, interior walls, ceilings, floors, stucco, natural stone, slate, marble, concrete, brick, render, statues, gypsum sculptures, wood, synthetic materials.

Property profile

Easy-Peel is an environmentally correct cleaning paste on a natural raw material base. The fresh product vulcanises by quickly drying into an elastic rubber with excellent dirt binding capacity.

Easy-Peel does not contain any organic solvents, surface active agents or inorganic salts.

Easy-Peel Cleaner can be used on its own for removal of soot and dirt from surfaces or with the addition of one of the Activators to give deeper cleaning.

The addition of Activator will not alter the drying time.

Characteristic data of the product

SG of Easy-Peel:	0.94	Off-White Liquid
SG of Activators:	0.99	Straw Colour Gel

Typical skinning times:

20 °C - 40% relative humidity	approx. 3 hours
20 °C - 65% relative humidity	approx. 3 hours
20 °C - 95% relative humidity	approx. 22 hours
5 °C - 65% relative humidity	approx. 23 hours
10 °C - 65% relative humidity	approx. 22 hours
20 °C - 65% relative humidity	approx. 3 hours
30 °C - 65% relative humidity	approx. 2.5 hours

Directions

Take care to protect surrounding areas before work with Easy-Peel begins. The surface to be cleaned must be dry and free of dust and loose soil deposits. Use of a vacuum cleaner is ideal for this.

Wear gloves and eye protection to prevent accidental splashes.

If you are using Easy-Peel with Activator you must thoroughly mix the two components together before starting.

Stir Easy-Peel well, then apply to the surface like a thick paint, with a paint brush, to ensure full covering of the entire surface.

Fill any corners, hollows, gaps and contours thoroughly with Easy-Peel.

Leave the product to dry fully for 24-48 hours before removal.

After the product has vulcanised, the resulting film is carefully removed from the top left towards the bottom right, keeping the degree of pull as constant as possible.

Surfaces treated with the Activated product should be cleaned again after the film has been peeled away by wiping off with a damp sponge, starting at the highest point.

When Easy-Peel is used without Activator, the surfaces do not need to be wiped down afterwards.

If necessary, a medium-hard nylon brush can be used for somewhat more intensive cleaning. As little water as possible should be used.

Notes

An introduction video on this technique of poultice peeling can be viewed on our website.

The specific mixing ratios for activated product must be strictly observed.

The selection of the type of Easy-Peel to be used depends on the condition of the substrate, type and intensity of soil and desired cleaning result.

Do not use on hot surfaces.

Tools

Paint Brush or Lambskin roller.
Gloves and eye protection.
Water to clean wet product.
Dried product can be removed by peeling off.

Protect skin from the product as the peeling action will also remove hairs!



Application rate, packaging, shelf-life

Application rate:

Approx. 0.7 - 1.0 kg/m² on smooth surfaces.

Up to approx. 3.0 kg/m² on textured, ornate or carved surfaces.

Packaging:

Easy-Peel	2.5kg tub
Activator for Marble	169g tub
Activator for Stone	639g tub

Each item is purchased separately.
One pack of Easy-Peel will cover up to 2.5m² depending on the profile and the thickness of film applied.

When mixed with the correct Activator this will be increased to a maximum coverage of 2.7m² for Marble and 3.1m² for Stone.

Shelf-life:

Max. 12 months stored dry and frost-free in original containers.

Activated material must be used within 1 week of mixing the components together.
Always re-mix again before use.

Safety, ecology, disposal

Further information on safety when transporting, storing and handling as well as disposal and ecology is found in the latest Safety Data Sheet.

The cured film once peeled away can be disposed of as normal household waste.



Remmers (UK) Limited Crawley
United Kingdom
Tel: +44(0) 845 373 0103
Fax: +44(0)845 373 0104
www.remmers.co.uk

Remmers (Far East) Pte. Ltd.
Singapore
Tel: +65 6 7410277
Fax: +65 6 7417158

The statements above are compiled from our field of production and according to the latest technological developments and application techniques.

Since application and working are beyond our control, no liability of the producer can be derived from the contents of this information sheet. Any statements made beyond the contents of this information must be confirmed in writing by the producer.

In all cases, our general conditions of sale are valid. With the publication of this Technical Information Sheet all previous editions are no longer valid.

Easy-Peel Cleaner-TI-08.07