



K-SEAL 'TOTAL' SEALER

DESCRIPTION.

Kingfisher K-SEAL TOTAL SEALER is the primary product of the K-Seal range. It is specifically designed to offer resistance to water, oil and petrol to many surfaces.

The product can be used on block paving bricks, concrete, flagstones and porous tiles and will provide enhanced colour as well as extending the life to the product.

Kingfisher K-SEAL TOTAL SEALER contains fungicide to provide resistance to the growth of algae, moss, lichen and weeds.

PREPARATION.

Remove all dirt, dust, algae, moss and lichen. Use **Kingfisher K-Seal BIO-CLEANER** to kill off all algal growth. Allow to dry.

APPLICATION.

Apply product, undiluted using a brush, roller or squeegee. Ensure no ponding occurs. Apply two coats for best results allowing 3 to 4 hours between coats.

Allow at least two full, dry days for treatment surface to be adequately dry for **K-SEAL TOTAL**. Application. (May require more than 48 hours in cold weather conditions).

MUST NOT BE APPLIED TO WET OR DAMP SURFACES!

COVERAGE.

Approximately 5 – 7 sq. metres per litre depending upon porosity of surface.

HEALTH and SAFETY.

Kingfisher K-SEAL TOTAL contains solvent aromatic middle distillate and is classified as harmful.

Do not apply to wet surfaces, in conditions of high humidity or when rain is forecast. (Protect from rain until dry.) Do not apply to non – porous surfaces.

Keep children and pets away from treated areas until fully cured.

Do not allow run off to contaminate drains, waterways or planted areas.

Kingfisher K-SEAL TOTAL is flammable and should be stored in a dry place away from sources of ignition or direct sunlight.

Read the Material Safety Data Sheet prior to using the product.

Further Health and Safety information on this product is provided on the MSDS, copies of which may be obtained from the Kingfisher Technical Dept. Tel. 01229 869100 or Fax. 01229 869101.

Kingfisher Product Information .76.