

Technical Information Sheet
Article No. 0671

Traffic Film Remover

Highly effective solution of surface-active agents

Range of use

Remmers Traffic Film Remover is used for the removal of grime, crusted dirt, dust and deposits of oil and grease on mineral substrates such as render, masonry work, concrete and natural stone.

Property profile

Remmers Traffic Film Remover is a highly effective surface-active agent solution for the removal of stubborn stains such as soot, dust, oily and greasy deposits. Optimal cleaning results are achieved through its strong washing action. Traffic Film Remover is low-foam and biodegradable. The product can be used for manual cleaning as well as for high pressure and steam cleaning equipment. It has a water softening effect.

Directions

Depending on the degree of soil and cleaning technique used, dilute Traffic Film Remover approx. 1:5 to 1:20 with water. Pre-wet absorbent substrates thoroughly. The cleaning agent should be thoroughly removed after cleaning with plenty of clean water. Residue from surface active agents may

Characteristic data of the product

Characteristic data of the produce in the packaged state

Appearance:	water based solution
pH value:	11.5
Density at 20°C:	1.00 kg/l
Surface active agent content:	approx. 10%

have a negative effect on subsequently applied impregnation agents with a water repelling effect.

Practice has shown that a waiting time of at least 3 weeks should be observed after cleaning before impregnation work can be carried out.

When using high pressure equipment, approx. 0.5% by mass Traffic Film Remover is added directly into the tank for chemicals.

Notes

Shake the container well before using or removing from the container. Do not use Traffic Film Remover to clean metals such as aluminium, zinc, copper and pewter. A trial area is recommended.

Tools, cleaning

Scrubber, brush, high pressure cleaner, steam cleaning equipment.

Packaging, application rate, shelf-life

Packaging:

5 l and 30 l plastic containers

Application rate:

Depending on type and degree of soiling, between 10-50 g/m².

Shelf-life:

At least 3 years stored dry and frost-free in closed, original containers.

Ingredients (EC-regulation 648/2004)

5 - 15% non-ionic surface active agents, less than 5% aliphatic hydrocarbons, less than 5% phosphonates, scents.

The statements above are compiled from our field of production and according to the latest technological developments and application techniques.

Since application and working are beyond our control, no liability of the producer can be derived from the contents of this information sheet. Any statements made beyond the contents of this information must be confirmed in writing by the producer.

In all cases, our general conditions of sale are valid. With the publication of this Technical Information Sheet all previous editions are no longer valid.



Remmers (UK) Limited Crawley
United Kingdom
Tel: +44(0) 845 373 0103
Fax: +44(0)845 373 0104
www.remmers.co.uk

Remmers (Far East) Pte. Ltd.
Singapore
Tel: +65 6 7410277
Fax: +65 6 7417158