



SAFETY DATA SHEET

Page 1 of 4

Restore-A-Drive

Revision 0
Revision date

1. IDENTIFICATION OF THE SUBSTANCE / PREPARATION AND THE COMPANY

Product name Restore-A-Drive
Company Kingfisher Building Products Ltd
Ulverston,
Cumbria LA12 9RA
kingfisheruk@tiscali.co.uk
www.kingfisheruk.com
Telephone 01229 869100
Fax 01229 869101
Emergency telephone number 01229 869100

2. COMPOSITION / INFORMATION ON INGREDIENTS

Hazardous ingredients

	Conc.	CAS	EINECS	Symbols/Risk phrases
1,2,4-Trimethylbenzene	10 - 20%	95-63-6	202-436-9	R10 Xn; R20 Xi; R36/37/38 N; R51/53
1,3,5-Trimethylbenzene	1 - 10%	108-67-8	203-604-4	R10 Xi; R37 N; R51/53
Xylene (Xylene, o-,m-,p-or mixed isomers)	1 - 10%	1330-20-7	215-535-7	R10 Xn; R20/21 Xi; R38
Cumene	0 - 0.5%	98-82-8	202-704-5	R10 Xn; R65 Xi; R37 N; R51/53
Low boiling point naphtha - solvent naphtha (petroleum), light arom.	10 - 20%	64742-95-6	265-199-0	Xn; R65
Low boiling point hydrogen treated naphtha - naphtha (petroleum), hydrotreated heavy.	40 - 50%	64742-48-9	265-150-3	Xn; R65 R10-53
2-methoxy-1-methylethyl acetate (1-Methoxypropylacetate)	0.5 - 1%	108-65-6	203-603-9	R10 Xi; R36
n-Butyl acetate (Butyl acetate)	0 - 0.5%	123-86-4	204-658-1	R10 R66 R67
Bis(1,2,2,2,6,6-pentamethyl-4-piperidyl) sebacate	1 - 10%	41556-26-7		Xi; R43 N; R50/53
Methyl 1,2,2,2,6,6-pentamethyl-4-piperidyl sebacate	0 - 0.5%	82919-37-7		Xi; R43 N; R50/53

3. HAZARDS IDENTIFICATION

Main hazards May cause sensitisation by skin contact. Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment. Harmful: may cause lung damage if swallowed.

Restore-A-Drive

Revision
Revision date

0

4. FIRST AID MEASURES

Skin contact	Wash off immediately with plenty of soap and water. Remove contaminated clothing. Seek medical attention if irritation or symptoms persist. May cause irritation to skin.
Eye contact	Rinse immediately with plenty of water for 15 minutes holding the eyelids open. Seek medical attention if irritation or symptoms persist. May cause irritation to eyes.
Inhalation	Inhalation may cause coughing, tightness of the chest and irritation of the respiratory system. Move the exposed person to fresh air. Seek medical attention. May cause irritation to respiratory system.
Ingestion	Harmful: may cause lung damage if swallowed. Ingestion may cause nausea and vomiting. Seek medical attention if irritation or symptoms persist. DO NOT INDUCE VOMITING. May cause irritation to mucous membranes.

5. FIRE FIGHTING MEASURES

Extinguishing media	Carbon oxides.
Fire hazards	Burning produces irritating, toxic and obnoxious fumes.
Protective equipment	Wear suitable respiratory equipment when necessary.

6. ACCIDENTAL RELEASE MEASURES

Personal precautions	Ensure adequate ventilation of the working area. Wear suitable protective equipment.
Environmental precautions	Do not allow product to enter drains. Prevent further spillage if safe.
Clean up methods	Absorb with inert, absorbent material. Sweep up. Transfer to suitable, labelled containers for disposal. Clean spillage area thoroughly with plenty of water.

7. HANDLING AND STORAGE

Handling	Avoid contact with eyes and skin. Ensure adequate ventilation of the working area. Adopt best Manual Handling considerations when handling, carrying and dispensing.
Storage	Keep in a cool, dry, well ventilated area. Keep containers tightly closed. Store in correctly labelled containers.

8. EXPOSURE CONTROLS / PERSONAL PROTECTION

Exposure limits

Xylene (Xylene, o-,m-,p-or mixed isomers)	WEL 8-hr limit ppm: 50 WEL 15 min limit ppm: 100	WEL 8-hr limit mg/m3: 220 WEL 15 min limit mg/m3: 441
Cumene	WEL 8-hr limit ppm: 25 WEL 15 min limit ppm: 50	WEL 8-hr limit mg/m3: 125 WEL 15 min limit mg/m3: 250
2-methoxy-1-methylethyl acetate (1-Methoxypropylacetate)	WEL 8-hr limit ppm: 50 WEL 15 min limit ppm: 100	WEL 8-hr limit mg/m3: 274 WEL 15 min limit mg/m3: 548
n-Butyl acetate (Butyl acetate)	WEL 8-hr limit ppm: 150 WEL 15 min limit ppm: 200	WEL 8-hr limit mg/m3: 724 WEL 15 min limit mg/m3: 966

Engineering measures	Ensure adequate ventilation of the working area.
Respiratory protection	Wear: Suitable respiratory equipment.
Hand protection	Chemical resistant gloves (PVC)
Eye protection	Approved safety goggles.
Protective equipment	Wear chemical protective clothing.

Restore-A-Drive

Revision 0
Revision date

9. PHYSICAL AND CHEMICAL PROPERTIES

Description	Liquid.
Colour	Black.
Odour	Characteristic.
Water solubility	miscible in water.

10. STABILITY AND REACTIVITY

Stability	Stable under normal conditions.
------------------	---------------------------------

11. TOXICOLOGICAL INFORMATION

Toxicological information	No data is available on this product.
----------------------------------	---------------------------------------

12. ECOLOGICAL INFORMATION

Ecotoxicity	May cause long-term adverse effects in the aquatic environment.
--------------------	---

13. DISPOSAL CONSIDERATIONS

General information	Dispose of in compliance with all local and national regulations.
Disposal methods	Contact a licensed waste disposal company. Dispose of in compliance with all local and national regulations. For disposal within the EC, the appropriate code according to the European Waste Catalogue (EWC) should be used.
Disposal of packaging	Empty containers can be cleaned with water. Do NOT reuse empty containers.

14. TRANSPORT INFORMATION

Further information	The product is not classified as dangerous for carriage.
----------------------------	--

15. REGULATORY INFORMATION

Labelling	The product is classified in accordance with 67/548/EEC.
------------------	--

Symbols	Xn - Harmful; N - Dangerous for the environment
----------------	---



Risk phrases	R43 - May cause sensitisation by skin contact. R51/53 - Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment. R65 - Harmful: may cause lung damage if swallowed.
Safety phrases	S1/2 - Keep locked up and out of the reach of children. S13 - Keep away from food, drink and animal feedingstuffs. S24 - Avoid contact with skin. S29 - Do not empty into drains. S37 - Wear suitable gloves. S46 - If swallowed, seek medical advice immediately and show this container or label. S62 - If swallowed, do not induce vomiting: seek medical advice immediately and show this container or label.

Restore-A-Drive

Revision 0
Revision date

16. OTHER INFORMATION

Text of risk phrases in Section 2

R10 - Flammable.
R20 - Harmful by inhalation.
R20/21 - Harmful by inhalation and in contact with skin.
R36 - Irritating to eyes.
R36/37/38 - Irritating to eyes, respiratory system and skin.
R37 - Irritating to respiratory system.
R38 - Irritating to skin.
R43 - May cause sensitisation by skin contact.
R50/53 - Very toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.
R51/53 - Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.
R53 - May cause long-term adverse effects in the aquatic environment.
R65 - Harmful: may cause lung damage if swallowed.
R66 - Repeated exposure may cause skin dryness or cracking.
R67 - Vapours may cause drowsiness and dizziness.

Further information

The information supplied in this Safety Data Sheet is designed only as guidance for the safe use, storage and handling of the product. This information is correct to the best of our knowledge and belief at the date of publication however no guarantee is made to its accuracy. This information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any other process.