

## NCC STONE SEALER & ENHANCER

### Water-dispersed Impregnating Sealer

#### Exterior and Interior use

For all types of natural and reconstituted stone, as well as other permeable mineral substrates, including tiles (e.g. ceramic & quarry tiles), brickwork and concrete. It is suitable for smooth (honed/polished) and rougher (sawn, split and blast cleaned) surfaces.

Colour enhancing water based impregnating sealer. Provides an enhanced natural finish. Helps protect against staining.

Strongly repels water, oil and grease. Allows surface to breathe. Helps reduce efflorescence.

## Directions for use

### Preparation:

Ensure surface to be treated is completely clean, dry and free from dirt, grime, cement and grout. If necessary, first wash surfaces with a dilute solution of **NCC Grime Remover** 1:10 and white pad. Rinse well to remove residues and leave to dry (24hrs).

**Rough cut, tumbled, textured or riven surfaces** Shake bottle before use. Apply generously and evenly using foam roller or paint brush. On more absorbent surfaces apply further coats at hourly intervals until the surface is fully saturated.

**Honed, smooth and polished surfaces** Shake bottle before use. Apply liberally and evenly using a sealant applicator pad, lint free cloth, lamb's wool applicator or sponge. Leave surfaces to dry.

On vertical surfaces apply from the bottom up.

## Coverage: M<sup>2</sup> per application

	1 LTR	5 LTR	25 LTR
Higher porosity surfaces	N/A	37.5m <sup>2</sup>	N/A
Medium porosity surfaces	N/A	75 m <sup>2</sup>	N/A
Honed smooth surfaces	N/A	150m <sup>2</sup>	N/A

## Aftercare

Routinely sweep clean and wash surfaces using a mild PH neutral detergent and clean water.

## Storage information

Store in a secure cool, dry, frost-free environment.

Shelf Life – Up to 2 years for un-opened containers.

This information is offered without guarantee. The material should be used so as to take account of the local conditions and the surfaces to be treated. In case of doubt, the product should be tried out in an inconspicuous area

## Other

Any dried on and over applied sealer can be removed by rubbing with damp micro fibre cloth, or on larger areas with a rotary machine with buffing pads. If dried on residues are left too long and difficult to buff away; apply a little soapy water and gently scrub with a white emulsifying pad, rinse and leave to dry.

Empty containers are recyclable. Active ingredients are water soluble and inert once cured.

For internal areas turn off under-floor heating prior to sealing. If in doubt, test on an inconspicuous area prior to general application. Avoid using strong detergents to wash treated surfaces. On higher porosity materials sufficient sealer should be applied until treated surfaces are fully saturated.

Do not use in temperatures under 5°C or over 25°C. Clean application tools and equipment with clean water after use.

## Health, Safety & Environmental

### Attention:

Keep out of reach of children.

Dispose of contents/container to a licensed waste centre in accordance with local /regional/national/international regulations.

